

## PRE-ASSEMBLED CONNECTORS



- Available as FC, SC, ST, LC, MTRJ, E2000 and MTP®/MPO
- Complies with IEC 61754-4, IEC 60784-14 and TIA 604-3
- RoHS, REACH SvHC compliant
- Low insertion loss and back reflection
- Zirconia ceramic ferrule with high end Ultra Physical Contact

### ORDERING INFORMATION

AC 1 2 3 4 5

1	CONNECTOR	2	FIBER TYPE	3	FIBER PORT	4	BOOT DIAMETER	3	PERFORMANCE
S1	SC	S	SINGLEMODE	S	SIMPLEX	9	900µm	S	STANDARD
S2	SCA	M	MULTIMODE	D	DUPLEX	2	2MM	P	PREMIUM
L1	LC					3	3MM		
L2	LCA								
F1	FC								
F2	FCA								
T1	ST								

## ADAPTERS



- Low insertion loss and improved reconnectability 01dB Maximum.
- Available in flanged and flangeless options.
- Supplied with zirconia ceramic sleeve.
- Complies with IEC 61754-4 standard

### ORDERING INFORMATION

AA 1 2 3 4 5

1	CONNECTOR	2	FIBER TYPE	3	FIBER PORT	4	FLANGE (ONLY SC/LC)	5	HOUSING COLOR (ONLY SCLC)
S1	SC	S	SINGLEMODE	S	SIMPLEX	F	FLANGE	L	BLUE
S2	SCA	D	MULTIMODE	D	DUPLEX	N	NO FLANGE	N	GREEN
L1	LC			Q	QUAD			E	BEIGE
L2	LCA							Q	AQUA
F1	FC							V	ERICA VIOLET
F2	FCA								
T1	ST								

## FIXED ATTENUATORS



- Low insertion loss and improved reconnectability 01dB Maximum.
- Blue, Green, Aqua and Erika Violet adaptors for SC & LC.
- Material compliant to RoHS2 and REACH SvHC.
- Available as FC, SC, ST, LC

### ORDERING INFORMATION

AT 1 2 3 4

1	CONNECTOR TYPE	2	FIBER MODE	3	CONNECTION	4	ATTENUATION	5	HOUSING COLOR (ONLY SCLC)
S1	SC SIMPLEX	S	SINGLEMODE	F	FEMALE TO MALE	1	1dB	L	BLUE
L1	LC SIMPLEX	M	MULTIMODE			2	2dB	N	GREEN
F1	FC SIMPLEX ROUND					3	3dB	E	BEIGE
						...	...	Q	AQUA
						30	30dB	V	ERICA VIOLET