


## MPO/MTP TRUNKS QSFP+ 40G



### FEATURES

- Conform to IEC, EIA-TIA, and Telcordia performance requirements
- All Assemblies are machine polished providing highest quality
- Cable terminated with low loss 8 fiber MPO Connectors.
- All Assemblies are factory tested and come with test certificate.
- Factory pre-terminated assemblies with protocol for constant and reliable quality.

### MPO/MTP CONNECTOR SPECIFICATION

Parameters	Units		Parameters	Units	APC
Max IL – Standard	dB	≤ 0.75	Average IL	dB	≤ 0.25
Return loss SM (PC/APC)	dB	≥ 60			
Max IL – Premium	dB	≤ 0.35	Average IL	dB	≤ 0.10
Return loss (PC/APC)	dB	≥ 60			

### ORDERING INFORMATION

MO\* 1 2 3 4 5 6 7 8 DIST\*\*

1	2	CONNECTOR	3	4	FIBER	5	CABLE CONSTRUCTION	6	JACKET COLOR	7	JACKET MATERIAL	8	POLARITY
G1	G1	8F MPO(F) STD	8	2D	G652D	D	MICROCABLE	Y	YELLOW	L	LSZH	B	POL B
G2	G2	8F MPO(M) STD		A1	G657A1	S	MICRO SINGLE	Q	AQUA	R	OFNR		
G3	G3	8F MPO(F) ELITE		A2	G657A2			V	ERIKA VIOLET	P	OFNP		
G4	G4	8F MPO(M) ELITE		O3	OM3								
				O4	OM4								

Example Part. No:

**MTG1G18A1SYB5**

QSFP Trunk MTP(F)-MTP(F) 8FO SM G657A1  
Microcable Single Yellow LSZH Polarity B 5Meters

\*For MTP/MPO from Usconec PN to be MT instead MO. Corning Fiber available on request.  
\*\*The length input stands for total length, from connector to connector.